

Order code	Product name	Closed ht. (m)	Open ht. (m)	Safe W/H (m)	Sec	Rungs per sec	Duty Rating kg/stone	Weight (kg)
570302	Ind. 500 1 Sec (P/U)	3.090	3.090	3.597	1	10	130/20.5	7.11
570304	Ind. 500 1 Sec (P/U)	4.250	4.250	4.687	1	14	130/20.5	9.65
570305	Ind. 500 1 Sec (P/U)	4.830	4.830	5.232	1	16	130/20.5	11.41
570312	Ind. 500 2 Sec (P/U)	3.115	5.145	5.527	2	10	130/20.5	13.94
570313	Ind. 500 2 Sec (P/U)	3.695	6.305	6.617	2	12	130/20.5	16.42
570314	Ind. 500 2 Sec (P/U)	4.275	7.465	7.707	2	14	130/20.5	21.06
570315	Ind. 500 2 Sec (P/U)	4.855	8.625	8.797	2	16	130/20.5	27.68
570316	Ind. 500 2 Sec (P/U)	5.435	9.785	9.888	2	18	130/20.5	33.50
570322	Ind. 500 3 Sec (P/U)	3.115	7.465	7.707	3	10	130/20.5	23.47
570323	Ind. 500 3 Sec (P/U)	3.695	9.205	9.342	3	12	130/20.5	33.45