



SAFETY DATA SHEET

INTUCRYLIC

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME: INTUCRYLIC

PART No.: 241831, 241848

SUPPLIER: BOSTIK FINDLEY LIMITED
COMMON ROAD
STAFFORD. ST16 3EH
STAFFORDSHIRE
Tel: +44 1785 272727
Fax: +44 1785 257236

EMERGENCY TELEPHONES: +44 1785 255141 +44 1785 272650

2. COMPOSITION/INFORMATION ON INGREDIENTS

| NAME | EINECS Nr.: | CLASSIFICATION | CONTENT |
|---|-------------|-----------------------|---------|
| AMMONIUM HYDROXIDE | 215-647-6 | C ,N R-34, 50 | 0-1 % |
| 1336-21-6 | | | |
| NAPHTHA (PETROLEUM), HYDROSULFURIZED HEAVY; LOW BOILING | 265-185-4 | Xn ,N R-10, 51/53, 65 | 0-1 % |
| 64742-82-1 | | | |

The Full Text for all R-Phrases are Displayed in Section 16

3. HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

4. FIRST AID MEASURES

GENERAL: General first aid, rest, warmth and fresh air.

INHALATION: Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION: DO NOT induce vomiting. Get medical attention immediately.

SKIN: Remove affected person from source of contamination. Rinse the skin immediately with lots of water. Get medical attention if irritation persists after washing.

EYES: Rinse the eye with water immediately. Continue to rinse for at least 15 minutes and get

medical attention.

5. FIRE FIGHTING MEASURES

| | |
|---------------------------------------|---|
| EXTINGUISHING MEDIA: | This material is not flammable. Use extinguishing media appropriate for surrounding fire. |
| HAZARDOUS COMBUSTION PRODUCTS: | Fire or high temperatures create: Toxic gases/vapors/fumes of: Carbon dioxide (CO ₂). Carbon monoxide (CO). |
| PROTECTIVE MEASURES IN FIRE: | Wear self contained breathing apparatus |

6. ACCIDENTAL RELEASE MEASURES

| | |
|--|--|
| PERSONAL PRECAUTION IN SPILL: | Avoid skin and eye contact. Ensure adequate ventilation. Wear personal protective equipment. |
| PRECAUTIONS TO PROTECT ENVIRONMENT: | Prevent entry into drains and water courses. |
| SPILL CLEANUP METHODS: | Stop leak if possible without risk. Do not contaminate water sources or sewer. Pick up with vacuum or absorbent solid, store in closed container for disposal. Avoid generation and spreading of dust. Avoid contact with skin or inhalation of spillage, dust or vapour. Wear necessary protective equipment. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. |

7. HANDLING AND STORAGE

| | |
|-----------------------------|--|
| USAGE PRECAUTIONS: | Avoid spilling, skin and eye contact. Do not handle broken packages without protective equipment. Use mechanical ventilation in case of handling which causes formation of dust. |
| STORAGE PRECAUTIONS: | Keep in cool, dry, ventilated storage and closed containers. Keep in original container. |

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

| INGREDIENT NAME: | CAS No.: | STD | LT EXP 8 Hrs | ST EXP 15 Min |
|---|------------|-----|-----------------------|---------------|
| NAPHTHA (PETROLEUM), HYDROSULFURIZED HEAVY; LOW BOILING | 64742-82-1 | OES | 600 mg/m ³ | |

INGREDIENT COMMENTS: OES = Occupational Exposure Standard. MEL = Maximum Exposure Limit.

PROTECTIVE EQUIPMENT:



VENTILATION: All handling to take place in well ventilated area.

PROTECTIVE GLOVES: Use suitable protective gloves if risk of skin contact. Use thin cotton gloves inside the rubber gloves if allergy risk.

EYE PROTECTION: If risk of splashing, wear safety goggles or face shield.

| | |
|---------------------------------|--|
| OTHER PROTECTION: | Wear suitable protective clothing as protection against splashing or contamination. |
| HYGIENIC WORK PRACTICES: | Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. No eating or drinking while working with this material. Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin. |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--------------------|------------------|
| APPEARANCE: | Paste or slurry. |
| COLOUR: | White. or Grey. |

10. STABILITY AND REACTIVITY

| | |
|------------------------------------|--|
| STABILITY: | Normally stable. |
| CONDITIONS TO AVOID: | Avoid excessive heat for prolonged periods of time. |
| HAZARDOUS POLYMERIZATION: | Unknown. |
| HAZARDOUS DECOMP. PRODUCTS: | Fire creates: Carbon monoxide (CO). Carbon dioxide (CO ₂). |

11. TOXICOLOGICAL INFORMATION

| | |
|-------------------|---|
| INGESTION: | Ingestion of this material may cause obstruction. |
| SKIN: | Liquid may irritate skin. |
| EYES: | Irritating to eyes. |

12. ECOLOGICAL INFORMATION

| | |
|--------------------------------|--|
| ECOLOGICAL INFORMATION: | Not regarded as dangerous for the environment. |
|--------------------------------|--|

13. DISPOSAL CONSIDERATIONS

| | |
|--------------------------|---|
| DISPOSAL METHODS: | Dispose of in accordance with Local Authority requirements. Recover and reclaim or recycle, if practical. |
|--------------------------|---|

14. TRANSPORT INFORMATION

| | |
|-----------------|------------------------------|
| GENERAL: | Not classified for transport |
|-----------------|------------------------------|

15. REGULATORY INFORMATION

NC Not classified

RISK PHRASES: Not classified.

SAFETY PHRASES: S-24/25 Avoid contact with skin and eyes.
S-39 Wear eye/face protection.

16. OTHER INFORMATION

USER NOTES: This product should be used as directed by Bostik Findley Ltd. For further information consult the product data sheet or contact Technical Services.

INFORMATION SOURCES: This safety data sheet was compiled using current safety information supplied by distributor of raw materials.

REVISION COMMENTS: This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Bostik Findley Limited.

ISSUED BY: Approved EC

REVISION DATE: April 2003

REV. No./REPL. SDS GENERATED: 1

DATE: April 2003

PRINTING DATE: 2004-04-22

R-PHRASES (Full Text): R-34 Causes burns. R-50 Very toxic to aquatic organisms. R-10 Flammable. R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R-65 Harmful: may cause lung damage if swallowed.